

CERTIFICATION OF TRANSLATION

" WASHING METHOD FOR A DISHWASHER, AND DISHWASHER
FOR CARRYING OUT ONE SUCH METHOD "

I, Rosamund Durham,

c/o Technisches Fachübersetzungsbüro, Försterweg 33, A-2136

Laa/Thaya, Austria,

am the translator of the documents attached and certify that
the following is a true translation to the best of my
knowledge and belief.



Signature of translator dated this 28th day of April, 2005

10/538050

- 1 -

JC17 Rec'd PCT/PTO 08 JUN 2005

WASHING METHOD FOR A DISHWASHER, AND DISHWASHER FOR
CARRYING OUT ONE SUCH METHOD

The subject matter of the invention is a washing
5 method, especially a method for determining and
generating a certain state of a washing program in a
dishwasher and a dishwasher for implementing this
method.

10 In conventional dishwashers whilst a washing program is
running, the respective state of the washing is
communicated to the user, e.g. by means of a time-
remaining display which indicates the time remaining
before the end of the washing program. This is also
15 carried out during the partial drying section of the
program. By means of this time remaining of the washing
program which is usually indicated in a display on the
front, the user who has sufficient experience with the
particular dishwasher, can reliably estimate when the
20 partial drying section of the program begins in the
particular washing program, i.e., the user can estimate
when the partial rinsing section of the program has
ended and if necessary, heating of the atmosphere in
the washing container for the purpose of drying the
25 washed items begins.

In conventional dishwashers, during so-called "adding
on" it is possible to briefly interrupt the washing
program by opening the dishwasher to receive crockery
30 in a washing program which has already begun. After
closing the dishwasher door, the washing program is
usually continued, i.e. a program controller saves the
state existing at the time of opening the dishwasher
door and after closing the dishwasher door, goes on
35 from precisely this time to continue the selected
washing program.

- 2 -

However, this usual interruption regulation for the washing program is disadvantageous for an interruption during the partial drying section of the program since
5 an interruption of the washing program during the partial drying section of the program by the user is not used to add items for washing but to completely interrupt the partial drying section of the program before the time remaining elapses and either to remove
10 the cleaned items immediately from the dishwasher or to speed up the drying process with the dishwasher door open.

If, following such a premature interruption of the partial drying section of the program, the dishwasher
15 which has meanwhile been emptied, is again loaded with dirty items and the washing program started, the program controller does not recognise that a new washing program is to be started but merely recognises,
20 as a result of the state stored in the program controller, that a program interruption has been made during the partial drying section of the program. After activating the program start, a countdown of the time remaining would begin and after this time remaining has
25 ended, the dishwasher would be in a readiness state but would not start the desired washing program. For example, if the partial drying section of the program is ended 6 minutes before its actual completion by opening the dishwasher door, after activating the next
30 program start a time remaining of 6 minutes must elapse before the user could activate the new washing program. The time delay and the associated double burden for the user of having to wait for a certain time remaining after a first activation of the washing program to re-
35 activate the dishwasher has proved disadvantageous.

- 3 -

The object of the present invention is thus to provide a method and a dishwasher able to differentiate between a desired brief interruption of the partial drying section of the program and an actual termination of the partial drying section of the program.

This object is solved by the method according to the invention having the features according to claim 1 and a dishwasher having the features according to the further independent claim. Advantageous further developments of the present invention are characterised in the dependent claims.

In the washing method according to the invention, following an interruption in a partial drying section of the program and once the program has been restarted, a parameter value is measured and compared with a pre-determined nominal value and if the measured parameter value deviates from the nominal value in a pre-determined manner, the selected program is set back to the beginning.

According to a preferred feature of the invention, following an interruption in a partial drying section of the program and once the program has been restarted, the temperature of a liquid in a dishwasher is measured and if the measured temperature is lower than the nominal value, the selected program is set back to the beginning.

More appropriately, the selected program is set back to the beginning immediately after the washing program has been activated.

The nominal value is preferably set at about 40° Centigrade.

- 4 -

In a dishwasher according to the invention comprising at least one program controller and comprising at least one sensor, following an interruption in a partial
5 drying section of the program and once the program has been restarted, a parameter value is measured by means of the sensor and compared with a stored pre-determined nominal value in the program controller, and if the measured parameter value deviates from the nominal
10 value in a pre-determined manner, the program controller sets the selected program back to the beginning.

According to a preferred feature of the invention, in
15 the dishwasher according to the invention the at least one sensor is at least one temperature sensor which is arranged and embodied to measure the temperature of a liquid in a pump reservoir of a circulating pump; that the dishwasher has means suitable for detecting an
20 interruption of the washing program at least during the partial drying section of the program and passing this on to the program controller and that following an interruption in a partial drying section of the program and once the program has been restarted, the
25 temperature of the liquid in a pump reservoir of a circulating pump of a dishwasher is measured using the temperature sensor and if the measured temperature is lower than the nominal value, the program controller sets the selected program back to the beginning.

30 More appropriately, the selected program is set back to the beginning immediately after the washing program has been activated.

35 The nominal value is preferably set at about 40° Centigrade.

- 5 -

Advantageously, the means for detecting the interruption of the partial drying section of the program is coupled to a door lock of the dishwasher so
5 that when the dishwasher door is opened, a signal is generated which initiates the activation of the method according to the invention in the program controller.

The method according to the invention is activated
10 according to the invention when the partial drying section of the washing program is interrupted by opening the dishwasher door. The interruption signal generated by the means for detecting the interruption of the partial drying section of the program, which is
15 coupled to the door lock of the dishwasher, is stored in the program controller and after the dishwasher door has been closed and the program run has been reactivated, results in measurement of the liquid temperature in the pump reservoir of the circulating
20 pump.

If a liquid temperature of 50°C or 60°C is present for example, the program controller assumes that the interruption of the partial drying section of the
25 program is such a short time ago that by shutting the dishwasher door and actuating the program selector switch, the user wished to continue the partial drying section of the program. However, if after activating the program selector switch and starting the program, a
30 liquid temperature of less than about 40°C is measured in the circulating pump, the program controller assumes that the interruption of the partial drying section of the program has at the same time resulted in complete termination of the partial drying section of the
35 program by the user and understands the activation of program starting as a re-start with the consequence

- 6 -

that the program controller sets the selected program back to the beginning, with the time remaining of the interrupted partial drying section of the program being set to zero and the initial value for the new washing
5 program being used as the running time (e.g. 73 minutes).

The present invention provides a method and a dishwasher able to differentiate between a desired
10 brief interruption of the partial drying section of the program and an actual termination of the partial drying section of the program.

The invention is explained in detail subsequently with
15 reference to the program flow diagram of a preferred exemplary embodiment of the method according to the invention shown in the single figure.

According to a preferred variant, the method according
20 to the invention is started with the opening and closing of a door of a dishwasher according to the invention in the partial drying section of the program wherein, after the washing program has been re-activated by the user, an interrogation routine begins
25 with a nominal/actual value comparison where the liquid temperature in the pump reservoir is interrogated as the parameter at a temperature sensor.

Since the nominal value in the exemplary embodiment
30 shown is specified as 40°C, if a liquid temperature of 40°C or colder is detected, the program controller terminates the partial drying section of the program and sets the old time remaining to zero. Instead, a new washing program is started and a new time remaining is
35 determined which corresponds to the program time of the selected washing program at the beginning of the new

- 7 -

washing program. After outputting the new time remaining, the method according to the invention is terminated.

- 5 If the liquid temperature is above 40°C, the program controller decides not to restart the washing program and the partial drying section of the program and the old time remaining continues to run. The method according to the invention is also terminated with this
10 action which is indistinguishable to the user.

The choice of temperature of 40°C for the nominal value can vary in different countries or regions, e.g. the nominal temperature can be specified as 50°C or a
15 higher temperature and equally as a temperature lower than 40°C.

The present invention provides a method and a dishwasher able to differentiate between a desired
20 brief interruption of the partial drying section of the program and an actual termination of the partial drying section of the program.